

Speed Enforcement

Specifications:

Weight: 2.75 lb (1 kg) with batteries
 Size: 7.75 x 3 x 11.75 in (20 x 8 x 30 cm)
 Acquisition Time: 0.33 sec
 Speed Accuracy: +/- 1 mph (+/- 2 kmh)
 Minimum Range
 Speed Mode: 50 ft (15 m)
 Weather Mode: 200 ft (76 m)
 Continuous Mode: 50 ft (15 m)
 Maximum Range: 2,000 ft (610 m)
 Speed Measurement
 Range: +/- 200 mph (+/- 320 kmh)
 Distance Accuracy: +/- 6 in (+/- 15 cm)
 Distance Resolution: +/- 1 ft (0.1 m)
 Beam Divergence: 2.5 milliradians nominal
 Laser Wavelength: 905 nanometers nominal
 Temperature Range: -22° F to +140° F (-30° C to +60° C)
 Power: Two alkaline, NiCad, or NiMH rechargeable C-cell batteries providing up to 25 hours of cordless operation.
 Eye Safety: FDA Class 1 (CFR 21)
 Environment: Water resistant / NEMA 4 / IP 55
 Construction: Composite Polycarbonate outer shell
 Aluminum internal chassis

Speed Mode	Weather Mode	Continuous Mode
LCD Backlight	Test Mode	HUD Brightness

